



MATERIAL	SS 304
FINISH	BUFFED

REQUIREMENTS—UNLESS OTHERWISE SPECIFIED	
GENERAL	
1. DIMS ARE IN MM (INCHES)	
2. INTERNAL RADII .015	
3. BREAK SHARP CORNERS	
LIMITS	
1. LINEAR DIMS.	
.XXX	= .005
.XX	= .010
.X	= .100
2. ANGLES = ± 1/2°	

CONTRACT NUMBER-	
CLIENT	-
CONTRACTOR	-
DRAWN	VRG
DATE	14/04/09
DESIGN	ASHISH
CHECKED	ASHISH
PROJECT	Q.A.
STRESS	MANUFACTURING
THERMAL	MATERIALS
MECHANISM	ELECTRICAL

NEX FLOW AIR PRODUCTS CORP.
 10520 YONGE STREET, UNIT 35B-220, RICHMOND HILL, ON L4C 3C7
 TEL.: (416) 410-1313 & FAX: (416) 410-1806 www.nex-flow.com

MACHINE NAME:				
MOUNTING BRACKET FOR 40001				
SIZE	CAGE CODE	PART NAME:	RELEASE	REV
C	-	40001MTS	P	0
SCALE	1:1	CAD NO	SHEET	OF
			1	1