

4

3

2

1

B

B

4X M6 THRD HOLES
(PER HALF) EQU SPC

SLOTTED BRACKET

Ø7.00

BRACKET

50.00°

15.00°

HOLE LOCATION PLUS BRACKETS

A

A

3/8 NPT
INLET

Ø5.00

9.96

15.02

Ø7.85

1.01

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
NEXFLOW. ANY REPRODUCTION IN PART
OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF NEXFLOW IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED		NAME	DATE
		DIMENSIONS ARE IN INCHES		DRAWN	AMMAD APR/23/21
		TOLERANCES:		CHECKED	
		FRACTIONAL ±		ENG APPR.	
		ANGULAR: MACH ± BEND ±		MFG APPR.	
		TWO PLACE DECIMAL ±		Q.A.	
		THREE PLACE DECIMAL ±			
		INTERPRET GEOMETRIC TOLERANCING PER:			
		MATERIAL			
		FINISH			
NEXT ASSY	USED ON	APPLICATION		DO NOT SCALE DRAWING	

NEX FLOW™ AIR PRODUCTS CORP.
10520 YOUNG STREET, UNIT 35B220, RICHMOND HILL, ON, L4C 3C7
TEL: (416) 410-1313 & FAX: (416) 410-1806 www.nexflow.com

TITLE:
5" RING BLADE

SIZE MODEL #: REV
B 20005 1

SCALE: 1:2.5 WEIGHT: SHEET 1 OF 1

4

3

2

1