



PROPRIETARY
 REPRODUCTION OR DISTRIBUTION
 WITHOUT WRITTEN CONSENT OF
 NEXFLOW™ IS PROHIBITED.

THIRD ANGLE PROJECTION		REQUIREMENTS—UNLESS OTHERWISE SPECIFIED				CONTRACT NUMBER	NEX FLOW AIR PRODUCTS CORP. 10520 YONGE STREET, UNIT 35B-220, RICHMOND HILL, ON L4C 3C7 TEL.: (416) 410-1313 & FAX: (416) 410-1006 www.nex-flow.com	
		GENERAL				CLIENT	1-1/2" THREADED HIGH TEMPERATURE STAINLESS STEEL RING VAC	
MATERIAL	HIGH TEMPERATURE STAINLESS STEEL	1. DIMS ARE IN INCHES (IN) 2. DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ASME Y14.5 (2002) 3. MACHINE FINISH 125 MICRO INCH RMS 4. INTERNAL RASH .015" (0-4) 5. BREAK SHARP CORNERS 0.005" (0.1) TO 0.015" (0.4)				DATE	25/04/2021	
FINISH	BUFFING	LIMITS				DESIGN	CHIRAGS	
		1. LINEAR DIMS. .001" = .005" (0.1) .002" = .010" (0.2) .005" = .030" (0.8) .010" = .050" (1.3) .015" = .075" (1.9) .020" = .100" (2.5)				LESS	LES	
		2. ANGLES = 2:1/2" 3. RUNOUT .010 TIR 4. HOLES IN ACCORDANCE WITH AND 10367				PRODUCT	GA	
		NEXT ASSEMBLY USED ON QTY PER PART NO PART NO ASBY				STRESS	MANUFACTURING	
						THERMAL	MATERIALS	
						Mechanism	ELECTRICAL	
						SCALE	1:1	
						DATE	30003THTS	
						REV	P	
						SHEET	1 OF 1	