



<p style="text-align: center;">PROPRIETARY REPRODUCTION OR DISTRIBUTION WITHOUT WRITTEN CONSENT OF NEXFLOW™ IS PROHIBITED.</p>						<p>REQUIREMENTS—UNLESS OTHERWISE SPECIFIED</p> <p>GENERAL</p>		<p>CONTRACT NUMBER —</p> <p>CLIENT —</p> <p>CONTRACTOR —</p>		<p>NEX FLOW AIR PRODUCTS CORP. 10520 YONGE STREET, UNIT 358-220, RICHMOND HILL, ON L4C 3C7 TEL: (416) 410-1313 & FAX: (416) 410-1806 www.nex-flow.com</p>									
				<p>MATERIAL</p> <p>HIGH TEMPERATURE STAINLESS STEEL</p>		<p>FINISH</p> <p>BUFFING</p>		<p>1. DIMS ARE IN INCHES (MM)</p> <p>2. DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5 (1982)</p> <p>3. MACHINE FINISH 125 MICRO INCH RMS</p> <p>4. INTERNAL RADI .015</p> <p>5. BREAK SHARP CORNERS .005 TO .015</p>		<p>LIMITS</p> <p>1. LINEAR DIMS. + .004 - .010 X .030</p> <p>2. ANGLES = ± 1/2°</p> <p>3. RUNOUT .010 TIR</p> <p>4. HOLES IN ACCORDANCE WITH AND 10387</p>		<p>DATE 25/04/2021</p> <p>DESIGN LES</p> <p>CHECKED LES</p>		<p>TITLE</p> <p>3" THREADED HIGH TEMPERATURE STAINLESS STEEL RING VAC</p>					
<p>NEXT ASSEMBLY</p> <p>USED ON</p> <p>QTY PER ASSEMBLY</p> <p>PART NO</p>		<p>PROJECT</p> <p>D.A.</p>		<p>STRESS</p> <p>MANUFACTURING</p>		<p>THERMAL</p> <p>MATERIALS</p>		<p>MECHANICAL</p> <p>ELECTRICAL</p>		<p>SIZE</p> <p>C</p>		<p>CHRG CODE</p> <p>30006THTS</p>		<p>DWG NO</p> <p>30006THTS</p>		<p>RELEASE</p> <p>P</p>		<p>REV</p> <p>—</p>	
<p>SCALE</p> <p>1:1</p>		<p>CAD NO</p>		<p>SHEET</p> <p>1</p>		<p>OF</p> <p>1</p>													