



Ø0.18" [Ø4.50]
3 HOLES, THRU

Ø0.18" [Ø4.50]
2 HOLES, THRU
ON 1.65" [42.00] PCD

PROPRIETARY
REPRODUCTION OR DISTRIBUTION
WITHOUT WRITTEN CONSENT OF
NEXFLOW™ IS PROHIBITED.

THIRD ANGLE PROJECTION	
MATERIAL	SS-304
FINISH	BUFFING

REQUIREMENTS—UNLESS OTHERWISE SPECIFIED	
GENERAL:	
1. DIMS ARE IN INCHES [MM]	
2. DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5 (1982)	
3. MACHINE FINISH 125 MICRO INCH RMS	
4. INTERNAL RADI .015	
5. BREAK SHARP CORNERS .005 TO .015	
LIMITS	
1. LINEAR DIMS.	XXX = .005
	XX = .010
	X = .030
2. ANGLES	+/- 1/2°
3. ROUNDT	.010 TH
4. HOLES IN ACCORDANCE WITH AND 10387	

CONTRACT NUMBER	—
CLIENT	—
CONTRACTOR	—
DRAWN	CHIRAG
DATE	30/01/2019
CHECKED	ASHISH
DESIGN	ASHISH
PROJECT	—
FINISH	—
MANUFACTURING	—
THERMAL	—
MATERIALS	—
Mechanism	ELECTRICAL

NEX FLOW AIR PRODUCTS CORP. 10520 YONGE STREET, UNIT 35B-220, RICHMOND HILL, ON L4C 3C7 TEL: (416) 410-1313 & FAX: (416) 410-1806 www.nex-flow.com					
MOUNTING BRACKET FOR 3/4" RING VAC					
SIZE	CAGE CODE	DWG NO	RELEASE	REV	
—	—	39000S	—	—	
SCALE	1:1	CAD NO	—	SHEET	1 OF 1