



PROPRIETARY
 REPRODUCTION OR DISTRIBUTION
 WITHOUT WRITTEN CONSENT OF
 NEXFLOW™ IS PROHIBITED.

THIRD ANGLE PROJECTION	
MATERIAL	SS-304
FINISH	BUFFING

REQS. UNLESS OTHERWISE SPECIFIED	GENERAL
1. DIMS ARE IN INCHES [MM]	
2. DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5 (1982)	
3. MACHINE FINISH 125 MICRO INCH RMS	
4. INTERNAL RADI .015	
5. BREAK SHARP CORNERS .005 TO .015	
LIMITS	
1. LINEAR DIMS	
"XXX" = .005	
".XX" = .010	
".X" = .020	
"X" = .050	
2. ANGLES = ± 1/2°	
3. RUNOUT .010 THR	
4. HOLES IN ACCORDANCE WITH AND 10387	

CONTRACT NUMBER	---
CLIENT	---
CONTRACTOR	---
DRAWN	CHIRAG.S
DATE	30/01/2019
DESIGNED	---
LES	---
PROJECT	---
QA	---
STRESS	---
MANUFACTURING	---
THERMAL	---
MATERIALS	---
ELECTRICAL	---
MECHANISM	---

NEX FLOW AIR PRODUCTS CORP. 10520 YONGE STREET, UNIT 35B-220, RICHMOND HILL, ON L4C 3C7 TEL: (416) 410-1313 & FAX: (416) 410-1806 www.nex-flow.com					
TITLE MOUNTING BRACKET FOR 3" RING VAC					
SIZE	D	CAGE CODE	---	DWG NO	39006S
SCALE	1:1	CAD NO	---	RELEASE	P 1
SHEET	1	OF	1		